



AIR BLOW GUN - HIGH BLOWING FORCE SILVENT 4020-L

Item number: 40200169064, 40200269064

SILVENT 4020-L: without adjustable blowing force. Suitable for applications where 100% power is always required. Otherwise, the same performance as 4020-LF.

Technical data

Replace open pipe Ø (mm)	25
Blowing force (N)	100.0
Air consumption (Nm ³ /h)	532
Sound level (dB(A))	118
Nozzle technology	Laval
Material (nozzle)	1.4305 (303)
Connection	G 3/4"
Connection type	Female
Weight (g)	770
Max temp (°C)	70
Max op. pressure (MPa)	0.7

Technical specifications

See basic information about the technical data. [Read more](#)

Benefits when replacing an open pipe

Replace open pipe Ø (mm)	25	
Noise reduction [dB(A)]	13 [dB(A)]	60%
Energy savings	627 [Nm ³ /h]	54%

Material specification: EN AB 43200, EN AW 2011 T8, EN 10088-3, NBR, PC, TPU EN AW 6082, EN 1.4305

Blowing properties at different pressures

Pressure (kPa)	200	400	600
Blowing force (N)	72.6		125.9
Air consumption (Nm ³ /h)	399.0		657.0
Sound level (dB(A))	113.0		120.0